
CNC MODULE WITH SOLID STATE RELAY

Features

- Designed for interfacing CNC Machine controllers having 24 inputs and 16 outputs with System Peripherals.
- Input Voltage 3-32V DC.
- Output Voltage 3-50V DC.
- Rated current 5A.
- Freewheeling Diode across relay coil for protection.
- 50 Pin FRC Connector.
- LED indication to denote relay actuation.
- Available with Pluggable relays, directly soldered on request.
- With Screw Terminals, Spring Terminals on request
- Mountable on Universal DIN Rail.



TECHNICAL INFORMATION

GENERAL DATA

| | •====== | | | |
|--|-------------------------------|---|-----------|--|
| | Input indication | 3 mm green LED for input status | Rated co | |
| | Relay protection | Free wheeling diode 1N4007 across relay coil | Minimum | |
| | Relay Socket | Paramount or equivalent | Maximum | |
| | Ambient operating temperature | 0°C to 50°C | Input Max | |
| | Housing material | PVC/V0 Grade, Phoenix Contact or equivalent | | |
| | Housing color | Green | | |
| | Conformal coating | Insulate, protect and seal electronic parts, available on request | | |
| | RoHS compliant | All the components used including PCBs are RoHS approved | | |

RELAY INPUT DATARated coil voltage24V DCMinimum voltage3V DCMaximum voltage32V DCInput Maximum current15.3 mA (for DC output)
17.3 mA (for AC output)

RELAY DATA Relay make Agility or equivalent Output voltage DC Relay approvals **Ç €**

| CONNECTION DATA | | RELAY OUTPUT DATA | |
|-----------------|---|--------------------------------|--------|
| Input | 50 Pin FRC connector | Nominal operating voltage | 24V DC |
| Make | Omron or equivalent | Minimum operating voltage | 3V DC |
| Output | PCB Terminals Screw (Nominal current: 24A, Rated voltage: 250V, Type of connection: Screw connection) | Maximum operating voltage | 50V DC |
| | | Maximum load current | 5A |
| | | Maximum turn on time | 100 µs |
| | Solid Min/Max: 0.2/4.0 mm² Stranded Min/Max: 0.2 / 2.5 mm² | Maximum turn off time | 960 µs |
| | | Input/Output isolation voltage | 2500V |
| Make | Phoenix Contact or equivalent | SSR output type | MOSFET |



24V Ext

> 24V Ext

24V Ext

24V Ext

С

 \supset

D

2

28

27

₽ 2

₽2

+24V DC

<mark>}</mark> ₹

0

O

0

Ο

SSR

SSR

 \sim

Article Nos. Descriptions Dimension LxWxH (mm) 11100341 AE-S-16-024D-1-B-CNC 312 x 90 x 65 Layout Diagram of AE-S-16-024D-1-B-CNC Layout Diagram of AE-S-16-024D-1-B-CNC 6 50 49 00 48 47 000 46 Ο Ο 8 8 8 **FRC 50** 000 Ō 31 Ο 000 000 30 Г 29 28 27 26 ŝ agility 2 i.

ORDERING INFORMATION

CNC Module with SSR Relay